

# Professional Landscape Fabric

Weed Control • Patio/Paver Underliner • Filter Fabric • Soil Separator

3 oz. Spunbond



ACTUAL SIZE FABRIC



## NO SAG PATIO/PAVER UNDERLINER

- Sand or aggregate won't sink into and intermix with soil
- Aggregate or sand base thickness can be reduced
- Prevents ground shifting, cracking, buckling and heaving
- Increases life of patio & driveway

## WEED CONTROL FABRIC

- Stops approx. 95% of weed growth
- Lets air, water and fertilizer pass through to plant roots
- Saves you time (no more weeding)
- Permanent when covered from sunlight

## FILTER FABRIC

- Protects native soil and silt from clogging drainage septic systems
- Drainage protection to maintain flow and percolation
- Prolongs life of septic drain fields and drainage pipes
- Proven alternative to graded aggregate or sand filters

## BENEFITS

- High strength to withstand heavy traffic
- Gives professional edge, available in retail & bulk
- Cuts quickly, no fraying
- Easy to install
- Permanent when covered from sunlight

## USE UNDER OR AROUND

- Patio Blocks & Pavers
- Decorative Stone & Bark
- Retaining Wall Filter Fabric
- Drainage and Septic Systems
- Sand

## TYPICAL SPECIFICATIONS

| Properties                        | Test Method   | 3 oz.                |
|-----------------------------------|---------------|----------------------|
| Unit Weight (oz/yd <sup>2</sup> ) | ASTM D-3776   | 3.0                  |
| Tensile Strength (lbs)            | ASTM D-4632   | 135                  |
| Elongation at Break (%)           | ASTM D-4632   | >70                  |
| Puncture Strength (lbs)           | ASTM D-4751   | 35                   |
| A.O.S. (equivalent sieve)         | ASTM D-4751   | 60/70                |
| A.O.S. (mm)                       |               | .24                  |
| Trap Tear (lbs)                   | ASTM D-4533   | 50                   |
| Coefficient of                    |               |                      |
| Permeability (cm/sec)             | ASTM D-4491   | 3 x 10 <sup>-2</sup> |
| Flux (gal/ft <sup>2</sup> /min)   | ASTM D-4491   | 70                   |
| Permittivity (sec <sup>-1</sup> ) | ASTM D-4491   | 1.3                  |
| Thickness (mils)                  | ASTM D-1777   | 15                   |
| Material                          | Polypropylene |                      |

## AVAILABLE SIZES

### Bulk Rolls

|          |              |      |
|----------|--------------|------|
| 3 x 250  | 750 sq. ft.  | 20#* |
| 4 x 250  | 1000 sq. ft. | 28#* |
| 5 x 250  | 1250 sq. ft. | 35#* |
| 6 x 250  | 1500 sq. ft. | 41#* |
| 8 x 250  | 2000 sq. ft. | 55#* |
| 10 x 250 | 2500 sq. ft. | 68#* |
| 12 x 250 | 3000 sq. ft. | 78#* |
| 15 x 250 | 3750 sq. ft. | 98#* |

\* Roll sizes & weights may vary.  
For best results the use of a pre and post emergent herbicide is advised.

**THE  
FABRIC CHOICE  
OF PROFESSIONAL  
LANDSCAPERS**



\* Refer to page 18 for installation instructions